



RITE-TEMP MFG.

SPECIFICATIONS:

- 240,000 BTU/HR heat removal 95F degree ambient, 45F degree water out.
- Electrical: 460 / 60/ 3Ph., 24 volt electrical panel.
- Run Load 45.95 Amps.
- Minimum Circuit Ampacity: 48; Maximum Circuit Ampacity: 86.
- ETL/CSA Laboratory Approved: ETL # 63122 & CANCSA NO. 236.
- (2) 40 gallon, 16 gage, 304 stainless steel closed evaporator tank with coil inside.
- 1.5 HP water pump: 25-30 GPM, 30-35 PSI.
- Low ambient start-up package (standard).
- R422D Refrigerant.
- Analog water temperature and pressure gauges.
- Air-cooled condenser.
- Cabinet: 18 and 20 GA Phos coat galvanized steel finished with polyester powder coat.
- Base frame: 1/8 inch angle and channel iron.
- Multi-compressor design: (4) 5 ton Copeland Hermetic (5 year warranty).
- Independent dual compressor operation for staged loads.
- Approximate crated weight: 2600 LBS.
- Condenser dimensions: 2 @ 30" wide X 58" deep X 32" tall.
- Evaporator dimensions: 54" wide X 60" deep X 47" tall.


RITE-TEMP MFG. MODEL: RTR-2004 CONDENSER Required - (2)





-58.0"

5/8" HIGH PRESSURE GAS INLET



1/2" HIGH PRESSURE GAS OUTLET