


- Electrical: 460 / 60/ 3Ph., 24 volt electrical panel.
- Run Load 59.9 Amps.
- Minimum Circuit Ampacity: 61; Maximum Circuit Ampacity: 110.
- ETL/CSA Laboratory Approved: ETL # 63122 & CAN/CSA NO. 236.
- (3) 40 gallon, 16 gage, 304 stainless steel closed evaporator tank with coil inside.
- 2 HP water pump: 25-30 GPM, 30-35 PSI.
- Low ambient start-up package (standard).
- R422D Refrigerant.
- Analog water temperature and pressure gauges.
- Air-cooled condenser.
- Cabinet: 18 and 20 GA Phos coat galvanized steel finished with polyester powder coat.
- Base frame: 1/8 inch angle and channel iron.
- Multi-compressor design: (5) 6 ton Copeland Hermetic Scroll (5 year warranty).
- Independent dual compressor operation for staged loads.
- Approximate crated weight: 3800 LBS.
- Condenser dimensions: 2 @ 39" wide X 58" deep X 34" tall & 1 @ 39" wide X 35" deep X 34" tall.
- Evaporator dimensions: 54" wide X 90" deep X 47" tall.




RITE-TEMP MFG. MODEL: RTR-3004 CONDENSER



REQUIRED - (2)

-39.0"-




5/8" HIGH PRESSURE GAS OUTLET

REQUIRED - (1)

7/8" HIGH PRESS. GAS INLET

5/8" HIGH PRESS. GAS OUTLET

ELECTRICAL OPENING BOTTOM OF CABINET



-35.0"--

NOT TO SCALE